

FireFly[®] 3

SOLAS Rescue Strobe Light



ACR Electronics, Inc.
5757 Ravenswood Rd.
Fort Lauderdale, FL 33312, U.S.A.
Tel Worldwide: +1(954) 981-3333
Fax: + 1(954) 961-4403
www.acrelectronics.com

COBHAM
Avionics & Surveillance

Product No.: 3995.3 carded
3995.4 bulk

Large sliding switch is easy to operate with gloved hands

Newly designed base platform allows unit to stand upright for hands free operation

1" webbing slots provide secure anchor points

360° high intensity Xenon strobe visible for up to 2 miles

Ideal for life vests, safety harnesses, float coats, work suits, immersion suits, backpacks, flight suits

Size: 4.75" x 2.2" x 1.2" (12.1 x 5.6 x 3 cm)

Weight: 3.8 oz (105 g) with lithium batteries

Material: Polycarbonate

Color: International orange

Operation: Slide switch up to ON position

Waterproof: Factory tested to 33 ft (10 m)

Beam Angle: .75 cd minimum (3.5 cd maximum) in all directions of upper hemisphere

Visibility: *Minimum 1 mile (.87 nm); to 2 miles (1.74 nm); may increase at higher altitudes or dry conditions

Flash Rate: 60± 10/minute, nominal

Lamp: High intensity Xenon strobe

Battery Type: 2- AA alkaline or 1.5 v lithium batteries
SOLAS approval with Lithium batteries only

Certification: USCG 161.012/58/0 (alkaline or lithium)
USCG SOLAS 131.112/58/0; IMO LSA Code
Res. MSC. 81(70); FAA TSOC 85 approved
(with lithium dated batteries only)

Operational Life: Minimum 8 hrs continuous at -1° C. Meets
USCG and IMO (SOLAS) specification

Carton Dimensions: Carded - 6.5" x 5.0" x 11"
(16.5 x 12.75 x 28 cm)

Units Per Carton: Carded- 6

Carton Weight: 1.9 lbs (.9 kg)

Limited Warranty: 1 year

*USCG Minimum luminous intensity of light

ACR Electronics, Inc. is registered by UL to ISO 9001: 2000